

## ZPMV2.E301197 - Wiring, Printed - Component

## Wiring, Printed - Component

ODAK PCB ELEKTRONIK ANONIM SIRKETI

E301197

Alkop Sanayi Sitesi B2  
Buyukcekmece, Blk 3-4 Turkey

Type	Cond Width		Cond	SS/ DSO	Max		Max		Assembly		Meets	C	
	Min	Edge			Area	Solder	Solder	Oper	Flame				
	Min	Edge	Thk	Diam	Limits	Temp	Class	UL796	Process	Temp	Flame	UL796	T
	mm(in)	mm(in)	mic(mil)	mm(in)	°C	sec	°C	Cycles	°C	Class	DSR	I	
<b>Multilayer printed wiring boards</b>													
<b>ML1</b>	0.10 (0.004)	0.10 (0.004)	16.5 (0.65) Int:66	DS	76.2 (3)	288	10	-	-	130	V-0	All	3
<b>ML2</b>	0.10 (0.004)	0.10 (0.004)	16.5 (0.65) Int:66	DS	12.7 (0.5)	288	10	-	-	130	V-0	All	3
<b>Single layer metal base printed wiring boards</b>													
<b>MC1</b>	0.12 (0.005)	0.12 (0.005)	35 (1.38)	SS	76.2 (3)	288	20	-	-	90	V-0	All	0
<b>MC2</b>	0.12 (0.005)	0.12 (0.005)	35 (1.38)	SS	76.2 (3)	288	20	-	-	130	V-0	All	0
<b>Single layer printed wiring boards</b>													
<b>1</b>	0.11 (0.004)	0.13 (0.005)	17 (0.67)	DS	75.9 (3)	288	10	-	-	130	V-0	All	3
<b>2</b>	0.11 (0.004)	0.13 (0.005)	17 (0.67)	DS	38.1 (1.5)	288	10	-	-	130	V-0	All	*
<b>3</b>	0.17 (0.007)	0.51 (0.02)	35 (1.38)	SS	76.2 (3)	260	10	-	-	105	V-0	All	*

\* - CTI marking is optional and may be marked on the printed wiring board.

NOTE - A triangle is marked on those products within a given type designation that comply with direct support of current-carrying parts performance level requirements of UL 796. "All" is used to indicate that all base materials under that type designation comply with direct support of current-carrying parts performance level requirement of UL796.

Marking: Company name, type designation. May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2021-05-28